

# CERTIFICATE OF COMPLIANCE

**Certificate Number** EX744  
**Report Reference** EX744-19720121  
**Date** 2021-September-15

**Issued to:** RELIABLE AUTOMATIC SPRINKLER CO INC  
1470 Smith Grove Rd  
Liberty SC, 29657 US

**This is to certify that representative samples of** VALVES, ALARM  
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL 193 - Standard for Alarm Valves for Fire-Protection Service  
ULC/ORD-C193-1975 - Standard for Alarm Valves for Fire-Protection Service

**Additional Information:** See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

Certificate Number EX744  
Report Reference EX744-19720121  
Date 2021-September-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

## Alarm Valves:

Model E, rated 175 psig, 65 mm, 2-1/2, 3, 4, 6, and 8 in. sizes for vertical and horizontal installation.

Model E, rated 175 psig, 4, 6 and 8 in. sizes for horizontal or vertical installation for use with the E-3 compact trim assembly.

Model E-3, rated 300 psig, 2-1/2, 3, 4, 6 and 8 in. sizes for horizontal or vertical installation for use with the E-3 compact trim assembly.

Model "E-1" retarding chamber with Model A or B strainer and with Model C water motor and gong (see Vol. 2).

Model "S-1" retarding chamber for use with Model E-3 Valve



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

